

**CLAIMS:**

- 1 1. A method of recovering a call between a wireless unit and a wireless  
2 communications system comprising the steps of:  
3 determining independently a second set of base station(s) by said wireless unit  
4 after a communication link between said wireless unit and a first set of serving base  
5 station(s) is severed; and  
6 changing from said first set of serving base station(s) for said call to a second  
7 set of serving base station(s) in attempting to service said call.
- 1 2. The method of claim 1 wherein said step of determining comprising:  
2 using information known at both the wireless communication system and at  
3 the wireless unit before the communication link was severed.
- 1 3. The method of claim 2 wherein said step of using including:  
2 using a candidate list identified with a previous pilot strength measurement  
3 message (PSMM) known to have been successfully reported to the wireless  
4 communications system.
- 1 4. The method of claim 3 wherein said changing including:  
2 automatically designating base station(s) in said candidate set as active.
- 1 5. The method of claim 4 further comprising:  
2 receiving a channel assignment message, over a control channel from at least  
3 one of said designated candidate base station(s), which provides at least forward  
4 channel assignments for said designated candidate base station(s).
- 1 6. A method of recovering a call between a wireless unit and a wireless  
2 communications system comprising the steps of:

3           determining independently a second set of base station(s) by said wireless  
4   communications system after a communication link between said wireless unit and a  
5   first set of serving base station(s) is severed; and  
6           changing from said first set of serving base station(s) for said call to a second  
7   set of serving base station(s) in attempting to service said call.

1   7.     The method of claim 6 wherein said step of determining comprising:  
2           using information known at both the wireless communication system and at  
3   the wireless unit before the communication link was severed.

1   8.     The method of claim 7 wherein said step of using including:  
2           using a candidate list identified with a previous pilot strength measurement  
3   message (PSMM) known to have been successfully reported to the wireless  
4   communications system.

5   9.     The method of claim 8 wherein said step of changing including:  
          automatically designating base station(s) in said candidate set as active.

1   10.    The method of claim 9 further comprising:  
2           transmitting a channel assignment message, over a control channel from at  
3   least one of said designated candidate base station(s), which provides at least forward  
4   channel assignments for said designated candidate base station(s).

1   11.    A wireless unit comprising:  
2           processing circuitry configured to determine independently a second set of  
3   base station(s) after a communication link carrying a call between said wireless unit  
4   and a first set of serving base station(s) is severed and further configured to change  
5   from said first set of serving base station(s) for said call to a second set of serving  
6   base station(s) in attempting to service said call.

- 1 12. A wireless communications system comprising:
- 2 processing circuitry configured to determine independently a second set of
- 3 base station(s) after a communication link carrying a call between said wireless unit
- 4 and a first set of serving base station(s) is severed and further configured to change
- 5 from said first set of serving base station(s) for said call to a second set of serving
- 6 base station(s) in attempting to service said call.